

Stemlock, Inc.

4200 NE Port Drive

Lee's Summit MO 64064

Tel: 800-795-0714

Fax: 816-795-7718



MaxBlast Stemming Plugs
US Patent # 5,841,060

Flexible Vinyl Plug

Friction Fit - Installs in Seconds

Simply push in point down with
a charging pole.

Positive Seal Prevents Gas
passage up the bore hole



[This versatile blasting accessory can be used in:](#)

Surface Applications as a Stemming Plug

Underground Applications to load horizontal or
upholes

Create Air Decks

Mark hole patterns for driller

Seal the top of the hole to prevent
contamination.

Use multiple plugs in place of stemming.

Used all over the world.

MB0100	1"	25mm
MB0125	1 1/4"	32mm
MB0150	1 1/2"	38mm
MB0175	1 3/4"	44mm
MB0200	2"	51mm
MB0225	2 1/4"	57mm
MB0250	2 1/2"	64mm
MB0300	3"	76mm
MB0350	3 1/2"	89mm
MB 0400	4"	102mm
MB0450	4 1/2"	114mm
MB0500	5"	127mm
MB0550	5 1/2"	140mm
MB0600	6"	152mm

[Inexpensive and invaluable](#)

Max-Blast Plugs are slightly oversized. However, stretching during insertion insures a tight fit in the bore hole. Max-Blast plugs will not damage down lines. Max-Blast plugs have been used successfully in Quarrying, Construction and Mining applications.